


Position	Count	Description
	1	<p data-bbox="343 340 614 369">Unilift AP35.40.08.A1.V</p> <div data-bbox="459 392 619 772" style="text-align: center;">  </div> <p data-bbox="734 772 1189 795" style="text-align: center;">Product photo could vary from the actual product</p> <p data-bbox="343 801 710 862">Product No.: 96001897 Submersible drainage pump type</p> <p data-bbox="343 891 869 1041">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase totally enclosed motor in insulation class F with thermal overload protection.</p> <p data-bbox="343 1070 813 1131">The pump is fitted with suction strainer and level switch for automatic start and stop.</p> <p data-bbox="343 1160 813 1276">The impeller is a VORTEX impeller for 1 3/8 in free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p data-bbox="343 1305 869 1400">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="343 1429 861 1545">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="343 1574 869 1758">The pump is ready for use as it is fitted with carrying handle and is supplied with a 16.41 ft mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="343 1787 885 1904">Liquid: Pumped liquid: any viscous fluid Liquid temperature range: 32 .. 131 °F Density: 62.29 lb/ft³</p> <p data-bbox="343 1933 805 2027">Technical: Type of impeller: VORTEX Maximum particle size: 1 3/8 in</p> <p data-bbox="343 2056 869 2105">Materials: Pump housing: Stainless steel</p>



Company name:

Created by:

Phone:

Date:

7/30/2018

Position	Count	Description
		DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304
		Installation: Pump outlet: Rp 1 1/2 Maximum installation depth: 6.562 ft
		Electrical data: Type of motor: PSC Power input - P1: 1.2 kW Main frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 5.5 A Cos phi - power factor: 0.98 Rated speed: 2795 rpm Capacitor size - run: 16 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 16.41 ft Type of cable plug: SCHUKO
		Others: Net weight: 28 lb Gross weight: 29.3 lb