


Position	Count	Description
	1	<p data-bbox="344 338 616 365">Unilift AP50.50.08.A1.V</p> <div data-bbox="429 389 619 775" style="text-align: center;">  </div> <p data-bbox="735 770 1190 797" style="text-align: right;">Product photo could vary from the actual product</p> <p data-bbox="344 801 708 860">Product No.: 96010584 Submersible drainage pump type</p> <p data-bbox="344 891 871 1039">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase totally enclosed motor in insulation class F with thermal overload protection.</p> <p data-bbox="344 1070 815 1128">The pump is fitted with suction strainer and level switch for automatic start and stop.</p> <p data-bbox="344 1160 831 1272">The impeller is a VORTEX impeller for 1 15/16 in free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p data-bbox="344 1303 874 1393">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="344 1424 863 1536">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="344 1568 874 1747">The pump is ready for use as it is fitted with carrying handle and is supplied with a 16.41 ft mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="344 1778 890 1899"> Liquid: Pumped liquid: any viscous fluid Liquid temperature range: 32 .. 131 °F Density: 62.29 lb/ft³ </p> <p data-bbox="344 1930 815 2020"> Technical: Type of impeller: VORTEX Maximum particle size: 1 15/16 in </p> <p data-bbox="344 2051 868 2110"> Materials: Pump housing: Stainless steel </p>



Company name:

Created by:

Phone:

Date:

7/30/2018

Position	Count	Description
		DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304
		Installation: Pump outlet: Rp 2 Maximum installation depth: 6.562 ft
		Electrical data: Type of motor: PSC Power input - P1: 1.3 kW Main frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 5.9 A Cos phi - power factor: 0.99 Rated speed: 2790 rpm Capacitor size - run: 16 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 16.41 ft Type of cable plug: SCHUKO
		Others: Net weight: 33.3 lb Gross weight: 35.1 lb